

# T300si Remote

## remote electric shower



Dimensions given are approximate

Temperature Control	Stabilised
Power Ratings	8.5 kW, 9.5 kW, 10.5 kW
Inlet Connection	15mm compression
Water Entry Points	Bottom, back (right hand side unit)
Cable Entry Points	Top, back (right hand side unit)
Outlet Connection	1/2" BSP
Plumbing System	Cold water only
Minimum Running Pressure/Flow	1 Bar @ 8 l/min and 1.5 Bar @ 1 l/min for 10.5 kW
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, CE, BSI kite mark
Guarantee	2 years

### Operating Features

- Low voltage wired technology

- Discrete control panel that operates up to 3.5m away from power pack
- Through the wall bulkhead riser rail
- Push button start/stop with phased shutdown
- Push button power selector for cold/economy/high
- Temperature control with numbered dial
- Low pressure indicator
- Rub clean showerhead – 5 spray pattern

Finish	Power	Code
All White	8.5 kW	SP3048SI
All White	9.5 kW	SP3049SI
All White	10.5 kW	SP3041SI
White/Chrome	8.5 kW	SP3008SI
White/Chrome	9.5 kW	SP3009SI
White/Chrome	10.5 kW	SP3001SI