

# Omnicare Ultra Align

Thermostatic Electric Shower

## Product Codes

Omnicare Ultra Align 8.7kW	CINCULT08W
Omnicare Ultra Align 9.8kW	CINCULT09W

## Installation

- Multiple pipe and cable entry points, a generous footprint, the Omnicare Ultra Align is designed with ease of replacement in mind
- Suitable for connection with an analogue waste pump

## Commissioning

- Simple 2 minute commissioning process

## End User

- Large soft press start/stop button
- Power on illumination along with audible feedback allows ease of use for all users
- Tactile temperature dial with soft grey tones offers helpful visual contrast
- SafeSet™ limits the maximum water temperature to 43°C, in line with guidance from our consultants in the OT Service. The unit can alternatively be configured to 41°C, meeting the BEAB Care Standard or a higher maximum temperature
- Tri-Care™ technology keeps the water temperature within +/- 1°C complying with BEAB care approval
- Set the duration of the shower ranging from 5 minutes to 30 minutes
- Easy clean 5 spray pattern shower head, with removable faceplate
- Single hand operated handset holder with easy push system




SAFETY CRITICAL  
TRITON ACCESSORY

# Omnicare Ultra Align

Thermostatic Electric Shower

## Shower

Temperature stability	Thermostatic +/-1°C with Tri-Care™ (1)
Power ratings	8.7kW & 9.8kW (at 240V)
Finish	White
Adjustable max temperature	41°C, 43°C or Max
Timed auto shutdown	5, 10, 20 or 30 mins (default 20 mins)
Start/stop type	Electronic soft press button
Controls	Start/stop button & temperature control dial
Audible feedback	Start/stop and timer end confirmation
Visual indicators	Power-on/timer/low flow illumination
Water connection	½" BSP male thread for 15mm compression fitting (swivel inlet (up/down))
Terminal block	16mm² max cable
Waste pump connection(s)	Analogue
Water supply	Mains cold water
Water pressure min	Minimum maintained pressure: 0.5 bar Minimum maintained pressure for BEAB Care: 1.0 bar
Water pressure max	10 bar (static)
Removable pipe/cable trims	Top & bottom
Other installation aid(s)	Wall mounting template



**Diagram Key:**

Water Entry Points

Cable Entry Points

**Dimensions:**

H: 400mm  
W: 213mm  
D: 117mm



## Riser Rail Kit

**Standard version**

Length	680mm
Diameter	25mm
Material	Stainless Steel
Finish	Polished
Hose	1.5m Anti-twist Chrome

### IMPORTANT MAINTENANCE NOTICE

Replacing specified Triton accessories for this Omnicare unit will aid optimum performance and keep the unit within the allocated guarantee period



Omnicare Kit  
(680mm) White  
GAUF1



1.5m Anti-twist Hose - Chrome  
REHOSE150C



Inclusive Showerhead  
(5 Spray Pattern)  
TSHECAREWHT

Contact our specification team

Call: 02476 324 776 | Email: [specification@tritonshowers.co.uk](mailto:specification@tritonshowers.co.uk) | Web: [www.tritonshowers.co.uk/specifiers](http://www.tritonshowers.co.uk/specifiers)